


Converter Box Series Hardware Specification	
<b>Model</b>	SDI 2 VGA (SDI2VGA-S)
<b>Product Photo</b>	
<b>Description</b>	<p>Converts from SDI to VGA. Provides two additional SDI outputs with repeater function.</p>
<b>Feature</b>	<ul style="list-style-type: none"> <li>● Auto source format detection (3G/HD/SD)</li> <li>● Built-in hardware scaling engine with anti-aliasing</li> <li>● Simultaneous 1 x VGA and 2 x SDI output</li> <li>● Splitter function</li> <li>● Re-clock function (for SDI output)</li> <li>● 1 Mini-USB port used for: <ul style="list-style-type: none"> <li>➢ Brightness, contrast, hue, saturation, configuration</li> <li>➢ Firmware upgrade</li> </ul> </li> </ul>
<b>Input</b>	SDI x 1
<b>Output</b>	D-Sub x 1 SDI x 2
<b>SDI Format</b>	3G-SDI (SMPTE 424M/425M) HD-SDI (SMPTE 292M) SD-SDI (SMPTE 259M)
<b>Supported Video Format</b>	640x480@60Hz 800x600@60Hz 1024x768@60Hz 1280x720@60Hz 1280x1024@60Hz 1400x1050@60Hz 1440x900@60Hz 1600x1200@60Hz 1920x1080@60Hz
<b>Supported Audio Format</b>	Up to 8 channels, 24bit, 48KHz (only available with SDI Loop-through output)
<b>Plug &amp; Play</b>	✓
<b>DC In</b>	6V ~ 15V