

VBOX-3611-POE

Intel Gen6 Core i7-6600U CPU with 4x POE Ports On-Board Computer



Delay Time



Power Ignition



Wide Range



Wireless



Battery Backup

Features

- Intel Core i7-6600U
- Wireless support LTE, 3.5G w/ SIM Card, WLAN
GPS Dead Reckoning, GSM/GPRS, BT
- Support 4 x Power Over Ethernet (POE)
- Smarter Vehicle Power Ignition for Variety Vehicle
- Support Dual Hot Swappable SATA Storage
- Support 1 x CAN Bus 2.0B (Optional)

Taiwan Patent No. M447854
Taiwan Patent No. M448011

System

CPU	Intel Gen 6 Core i7-6600U 2.6GHz up to 3.4GHz Intel Gen 6 Core i5-6300U 2.4GHz up to 3.0GHz Intel Gen 6 Core i3-6100U 2.3GHz Intel Gen 6 Dual Core 3955U 2.0GHz
Memory	2 x DDR4L 2133 MHz SO-DIMM up to 32GB
Chipset	Intel 6th Generation Core SoC Processor
LAN Chipset	Intel I210-AT Gb/s Ethernet Controllers Onboard Support PXE and WOL
Audio	Realtek ALC662 HD Codec Onboard
Watchdog	Watchdog Timer Support, Offer 1 – 255 Step

I/O

Serial Port	3 x RS-232 (2 with RS-422/485 (Auto Direction Control))
USB Port	2 x USB 3.0 Ports, 2 x USB 2.0 Ports
LAN	4 x M12 Ports for GbE POE (IEEE802.3AF 15.4W per port)
Video Port	1 x DVI-I*, 1 x DP Port, 1, VGA (Support Triple Independent Display)
DIO Port	4 In and 4 Out
Audio	1 x Line-out and 1 x Mic-in (Line-in Optional)
SIM Card Socket	1 x SIM Card Socket Supported Onboard with eject

* Use only with Single Link DVI Cables.

Graphics

Graphics	Intel® HD Graphics 520 DirectX Video Acceleration (DXVA) for Accelerating Video Processing - Full AVC/VC1/MPEG2 HW Decode Supports DirectX 11/10.1/10/9 and OpenGL 4.0
Resolution	Max Resolution (HDMI1.4) : 4096x2304@24Hz Max Resolution (DP) : 4096x2304@60Hz

Storage

Type	2 x 2.5" Drive Bay for SATA Type HDD/SSD, Support RAID 0, 1 1 x mSATA
-------------	--

Power Requirement

Power Input	9V - 36V DC Power Input
Power Protection	Automatics Recovery Short Circuit Protection
Power Management	Vehicle Power Ignition for Variety Vehicle
Power Off Control	Power off Delay Time Setting by Software and BIOS
Battery (UPS)	Internal Battery Kit for 10 Mins Operating (Optional)

Patent No. : M447854 - Build-in Battery

Environmental

Operating Temp.	-40°C ~ 70°C (Default CPU 17Watt)
Storage Temp.	-40°C ~ 80°C
Relative Humidity	0% RH – 95% RH
Vibration(random)	2.5g@5~500 Hz with SSD
Vibration Operating	MIL-STD-810G, Method 514.5, Category 20, Ground Vehicle-Highway
Truck Storage	MIL-STD-810G, Method 514.5, Category 24, Integrity Test
Shock	Operating: MIL-STD-810G, Method 516.5, Procedure I, Trucks and semi-trailers=15G (11ms) with SSD
Crash Hazard	MIL-STD-810G, Method 516.5, Procedure V, Ground equipment=100g
Certifications	CE, FCC Class A, E-13, EN50155, EN50121

Mechanical

Construction	Aluminum Alloy
Mounting	Supports Both of Wall-mount/VESA-mount
Weight	1980 g (Barebone)
Dimensions	250 x 150 x 55 mm

Ordering Information

Part Number	VBOX-3611-POE-XXX
Description	Intel Gen6 Core i7-6600U CPU with HD 520 GPU and 4x POE Ports On-Board Computer