

Hardware Specification	
<b>Model</b>	<b>VDB5A0 N1 MC SDI</b>
<b>Max. Input Resolution</b>	60/50fps @ 1920x1080p
<b>Recording Mode</b>	Hardware Compression, Real-Time Mode
<b>Product Photo</b>	
<b>Dimension</b>	30 x 50.95 (mm)
<b>Interface</b>	Minicard (PCIe x1)
<b>Video Input</b>	1 x SDI
<b>Video Output</b>	1 x SDI (loop-through output)
<b>RAW Data Format</b>	YV12
<b>RAW Data Video Resolution</b>	1920x1080p@30/25/24fps 1920x1080i@60/50fps 1280x720p@60/50fps 720x480i@60fps 720x576i@50fps
<b>Recording Video Format</b>	H.264 High Profile (Hardware Compression)
<b>Recording Video Resolution</b>	1920x1080p@30/25/24fps 1920x1080i@60/50fps 1280x720p@60/50fps 720x480i@60fps 720x576i@50fps
<b>Audio Input</b>	SDI Embedded Audio Audio L/R (2 x RCA through wafer connector to RCA cable)
<b>Audio Format</b>	Stereo / 16-bit / 32000 ~ 48000Hz
<b>Multiple Cards</b>	∞
<b>SDK</b>	VC++ / .NET / VB
System Requirement	
<b>OS Support</b>	Windows XP / Vista Windows 7 / Windows 8 / Windows 8.1 ( 32-bit and 64-bit )